

Xprinter®

## Impact Dot matrix Printer

# XP-76IIN




- Support GB18030
- Three-ply capable
- Black mark orientation
- Bi-directional printing














# XP-76IIN

## Impact Dot matrix Printer







| Printing | XP-76IIN |
|---|---|
| Printing method | 9-Pin serial impact dot-matrix printing |
| Printing width | 63.5mm |
| Print Resolution | 84 dpi |
| Printing speed | 4.5 line/s |
| Interface | Parallel/USB |
| Print paper | 75.5±0.5mm φ65mm |
| Character size | ANK, Font A: 1.6×3.1mm（9×9 dots） Font B: 1.2×3.1mm（7×9 dots）<br>Chinese, traditional Chinese: 2.7×2.7mm（16×16 dots） |
| Column number | Font A - 33 columns /Font B - 40 columns /<br>Chinese, traditional Chinese - 22 columns |
| **Character** | |
| Extension character sheet | PC437/Katakana/PC850/PC860/PC863/PC865/WPC1252/PC866/PC852/PC858 |
| **Software** | |
| Driver | Windows /Linux /Mac |
| Utility | Windows |
| SDK | Windows/ Android |
| **Power** | |
| Power adaptor | Input： AC 110V/220V, 50 ~ 60Hz,<br>Output: DC 24V/2.5A |
| Printer input | DC 24V/2.5A |
| **Physical characteristics** | |
| Weight | 1.46KG |
| Dimensions | 230*150*138mm (D×W×H) |
| **Environmental Requirements** | |
| Work environment | 0 ~ 45℃, 10 ~ 80% RH |
| Storage environment | -10 ~ 60℃, 10 ~ 90% RH（no condensation） |
| **Reliability** | |
| Printer head life | 10 Million Lines |

Scan QR code to checkout Xprinter website for more update information.
Phone: (+86 756) 3895 852
Http://www.xprintertech.com
Email: overseas@xprinter.net

Windows 7 Windows 8 Windows 10