





XP-TS80


Panel Printer



- Support QR CODE Printing
- Support wall mountable and truck cable
- Change IP through Web or Serial port
- Support overtype function






XP-TS80
Panel Printer

QR CODE | EASY LOAD | COMPACT DESIGN | HIGH SPEED | AUTO CUTTER | VARIOUS INTERFACE | PAPER WIDTH



Model	XP-TS80
Printing method	Direct thermal
Paper width	79.5±0.5mm
Print width	72mm
Column capacity	576 dots/line
Print speed	200 mm/s Max.
Interface	USB+Serial
Line spacing	3.75mm
Character size	ANK, Font A：1.5×3.0mm（12×24 dots） Font B：1.1×2.1mm（9×17 dots） Chinese, traditional Chinese:3.0×3.0mm（24×24 dots）
Column number	Font A - 42 columns or 48 columns/ Font B - 56 columns or 64 columns/ Chinese,traditional Chinese - 21 columns or 24 columns
Barcode Character	
Extension character sheet	PC347(Standard Europe) / Katakana / PC850(Multilingual) / PC860(Portuguese) / PC863(Canadian-French) / PC865(Nordic) / West Europe / Greek / Hebrew / East Europe / Iran/WPC1252 / PC866(Cyrillic#2) / PC852(Latin2) / Pc858 / IranII / Latvian / Arabic / PT151(1251)
Barcode types	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128
2D Barcode	QR CODE
Input buffer	4096 Kbytes
NV Flash	256 Kbytes
Power	
Power source	Output：DC 24V/2.5A
Cash drawer output	DC 24V/1A
Physical characteristics	
Weight	1.8 KG
Dimensions	202.7 ×158×140 mm (D×W×H)
Environmental Requirements	
Operation environment	Temperature: 0~45℃ humidity : RH 10 ~ 80%
Storage environment	Temperature: -10~60℃ humidity: RH 10~90℃
Reliability	
Cutter life	1 million cuts
Printer head life	100 KM

Scan QR code to checkout Xprinter website for more update information.
Phone: (+86 756) 3895 852
Http://www.xprintertech.com
Email: overseas@xprinter.net

Windows 7 Windows 8 Windows 10